

1 Series

C Systems - IP-54 rated columnar array with LMT for large installations



Applications

- Fixed Installations
- Acoustically Challenging Venues
- Churches & Cathedrals
- Corporate AV
- Airports & Transportation Terminals
- Concourses

Features

- All systems are IPX-66 weather resistant for outdoor use
- Boxed with custom pan-tilt brackets for quick and accurate installation
- Multiple transformer taps for 70 V and 100 V line systems or 8 Ohm direct input
- Attractive aluminum design for corrosion free performance
- Ultra-wide 140 degrees horizontal coverage

Products in the Series

- VC 106 TW
- VC 104 TW

The C systems are engineered for challenging acoustic spaces where music and speech reinforcement is required, yet aesthetic importance is paramount. The C Systems columnar array loudspeakers are available in 4, and 6 full range transducer models, are high-quality 70V/100V or 8 ohm bypass, and are IP-65 rated for dust & splash resistance

British Acoustics

Creative Park, Langley Park,

Durham DH7 9TT, UK.

All Rights Reserved - British Acoustics

T: +44 191 373 7638

E: info@britishacoustics.com

www.britishacoustics.com

VC 106 TW

6 x 4" Columnar Array System

Technical Specifications

Frequency Range (+/- 10dB)	150 Hz - 20 kHz
Frequency Response (+/- 3dB)	170 Hz - 20 kHz
Coverage Pattern	140° x 20°
Max Spl	122 dB
LF Driver	6 x 4.5" Vero Loaded Drivers, 1" VC - Ferrite
Rated Power	150W Continuous, 600W Peak
Nominal Impedance	8 Ohms or 100/70 V
Transformer Taps	120W - 100 / 70V
Sensitivity	86 dB

General Specifications

Enclosure	Rugged ABS Housing, IP 66
Grill	Powder Coated rust-free grill
Finish	Sesimic Black Finish
Mounting System	Wall Mount Insertion Terminal
Height	28"
Width	8"
Depth	8"
Weight	16 Kgs



British Acoustics

Creative Park, Langley Park,

Durham DH7 9TT, UK.

All Rights Reserved - British Acoustics

T: +44 191 373 7638

E: info@britishacoustics.com

www.britishacoustics.com