

2 Series

Onyx-M Series - Leaves a trace in half the space! Onyx Mount Systems



Applications

- Fixed Installations
- Cafes, Bars & Restaurants
- Retail Outlets
- Corporate AV
- Hotels & Convention Centres
- Educational Offices
- HoW, leisure centres and retail outlet

Features

- Nano modularity enables designers to use upto 8 enclosures on one channel
- Series out switch makes installation easy
- Zero-resonance 4" Full range driver design
- Professional aesthetics to complement intricate venues
- Pole, Yoke and power mount options

Products in the Series

- Onyx 224
- Onyx 214

Perfect for installations where invisibility and fidelity are key factors. The Onyx mount systems use resonant free, high sensitivity 4" drivers that perform at high SPL levels and can master acoustic and architectural challenges in a wide range of installation applications ranging from BGM solutions to huddle rooms and more

British Acoustics

Creative Park, Langley Park,

Durham DH7 9TT, UK.

All Rights Reserved - British Acoustics

T: +44 191 373 7638

E: info@britishacoustics.com

www.britishacoustics.com

Onyx 224

Dual 4" Surface Mount Installation Speaker

Technical Specifications

Frequency Range (+/- 10dB)	144 Hz - 16 kHz
Frequency Response (+/- 3dB)	99 Hz - 18 kHz
Nominal Coverage	100° x 40°
Max Spl	127 dB
LF Driver	2 x 4" Full Range NanoModular Onyx Driver
Rated Power	80W Continuous, 320W Peak
Inputs	2 X TRS Jack Power Inputs, Wired Parallel
Nominal Impedance	8 Ohms
Crossover Frequency	N/A (Full Range Driver)
Sensitivity	98 dB

General Specifications

Enclosure	Birch Plywood Enclosure
Grill	Powder coated durable grill with acoustically Transparent foam
Finish	British Acoustics' Signature Brown Finish
Mounting System	Onyx Throne Wall Bracket
Height	11"
Width	2.6"
Depth	3"
Weight	7 Kgs

