

6 Series

PW Systems - The complete range of affordable live sound systems



Applications

- Portable sound reinforcement
- Live Sound Reinforcement
- Mobile Touring
- Stage monitoring
- Corporate AV events and conferences
- Infills & Side-Fills

Features

- Custom built transducers
- Extended low-frequency response for a true full range performance
- Ideal for FOH, Side-Fill & Floor Monitoring Use
- Perforated Steel Hex Grill
- Integrated Handles & Ergonomic design for easy transport
- Scratch Resistant Paint finish

Products in the Series

- PW 682
- PW 618
- PW 625
- PW 615
- PW 612
- PW 610

The PW series is designed to bring high fidelity, better coverage, and an increased dynamic range to economical PA systems. The systems use custom build drivers and layered ports for an enhanced performance. The entire range of loudspeakers is constructed using multi-layered plywood for added durability.

British Acoustics

Creative Park, Langley Park,

Durham DH7 9TT, UK.

All Rights Reserved - British Acoustics

T: +44 191 373 7638

E: info@britishacoustics.com

www.britishacoustics.com

PW682

Passive Dual 8" Full Range Speaker

Technical Specifications

Frequency Range	53 Hz - 20 kHz
Frequency Response	65 Hz - 20 kHz
Coverage Pattern	120° x 60°
Max Spl	120 dB
Rated Power	500W Continuous, 2000W Peak
Nominal Impedance	8 Ohms
LF Driver	2 x 8" LF Drivers, 3" VC - Ferrite
HF Driver	1" exit compression driver, 1.5" VC
Crossover Frequency	1.4 kHz
Sensitivity	94 dB

General Specifications

Enclosure	Birch Plywood Enclosure
Grill	Powder coated durable grill with acoustically Transparent foam
Finish	British Acoustics' Signature Brown Finish
Mounting System	Integrated Handles - M-10 insertion points - Pole Mounting Socket
Height	17"
Width	10"
Depth	9.8"
Weight	11 Kgs

