

8 Series

Octa Systems - Constant Directivity Active Line Array & Subwoofer System



Applications

- Live Sound Reinforcement
- Corporate AV Events and conferences
- Theatre Installations
- Fixed Installations
- Auditoriums & Seminar Halls
- Mobile Touring

Features

- 8 x 2" Tweeters mounted over a high power 12" woofer
- Preset / delay selection pots with quick & easy set-up
- Dual-lock rigging mechanism
- Near-field & Straight Pole mount options
- Single frame to fly or groundstack the system
- Constant 20-degree vertical coverage

Products in the Series

- Octacurve
- Octasub

The octa-curve line array is uniquely designed with a 12" woofer behind an array of 8, 2" tweeters for concise hf control. The built in Class-D amplification module features best in class filtering & processing technologies. The Octa-Sub is a flyable subwoofer that completes the system resulting in High SPL line array system that is truly easy to use

British Acoustics

Creative Park, Langley Park,

Durham DH7 9TT, UK.

All Rights Reserved - British Acoustics

T: +44 191 373 7638

E: info@britishacoustics.com

www.britishacoustics.com

OctaSub

Single 18" Powered Subwoofer Flyable

Technical Specifications

Frequency Range (+/- 10dB)	36Hz - 144Hz
Frequency Response (+/- 3dB)	42Hz - 140Hz
Dispersion (- 6dB)	Omni-directional
Max Spl	135 dB
Connection	Power-con Input & Link, Direct Line XLR Input & Link Output
Amplifier Power (peak)	2000 W
Amplifier Power (cont)	1000W
Controls	Preset Selector, Phase Invert, Signal, Clip Indicator
Transducers	18" Low Frequency Driver, Ferrite

General Specifications

Enclosure	Birch Plywood Enclosure
Grill	Powder coated durable grill with acoustically transparent foam
Finish	British Acoustics' Signature Brown Finish
Mounting System	Integrated Rigging Mechanism, Integrated Handles for easy transport
Optional Accessories	Octa-frame, Pole Mount (SPM-1), Weatherproof Covers, Flight Cases
Height	23"
Width	20.8"
Depth	24"
Weight	53 Kgs

