

1 Series

VA Systems - VA Versatile Application Systems



Applications

- · Fixed Installations
- · Cafes, Bars & Restaurants
- · Retail Outlets
- Corporate AV
- Hotels & Convention Centres
- Educational Offices

Products in the Series

- VA 116 XTW
- VA 114 XTW

Features

- · IPX-66 rated for environmental applications
- Integrated 70V transformer with a 8 ohms bypass
- · Pendant, Wall or Landscape modes
- · IPX-66 rated ABS enclosre
- · Co-herent phase response from aco-axial design

The VA indoor/outdoor multi-purpose speaker systems feature a 2-way coaxial design complete with a 6.5" or 4" woofer and 1" tweeter. The IP66 weather resistant ABS plastic construction is able to withstand outdoor environments while remaining aesthetically pleasing for indoor use. The VA systems can be used for both commercial and residential applications.

British Acoustics
Creative Park, Langley Park,
Durham DH7 9TT, UK.

T: +44 191 373 7638

E: info@britishacoustics.com

All Rights Reserved - British Acoustics

www.britishacoustics.com



VA 116 XTW

6" Versatile Application Speaker

Technical Specifications

Frequency Range (+/- 10dB)	91 Hz - 20 kHz
Frequency Response (+/- 3dB)	100 Hz - 20 kHz
Coverage Pattern	100° x 100°
Max Spl	119 dB
LF Driver	6" Weather Resistant Coaxial Driver
HF Driver	1" Dome Compression Drivers, 1.4" VC
Rated Power	30W Continuous, 120W Peak
Nominal Impedance	8 Ohms or 100/70 V
Sensitivity	95 dB
Transformer Taps	40W, 20W, 10W - 100 / 70 V



Enclosure	IPX 66 rated ABS Enclosure
Grill	Powder Coated rust-free grill
Finish	Sesimic Black Finish
Mounting System	Wall, Floor or Pendant Mounting Installation
	Kits
Height	6.75"
Width	6.75"
Depth	5.5"
Weight	3.5 Kgs







British Acoustics
Creative Park, Langley Park,
Durham DH7 9TT, UK.

E: info@britishacoustics.com